

ITA 41

STEEL STRAPPING TOOL > PNEUMATIC

Pneumatic Steel Strapping Tool for 19mm / 25mm / 32mm Steel Strap Double Notch with Seal Manual Tensioning operation

ITA 41 is the combined pneumatic strapping tool for 19mm / 25mm / 32mm steel strap.

The three operating buttons allow the manual tensioning of any type of Steel Strap (Standard and High Resistance), providing a Double Notch Sealing with seal.

Useful for strap flat, round and irregular packages, the ITA41 results suitable for intensive use and it will be also able to work in continuous cycles productions.

ITA 41 finds application in any sector, including the heaviest industries like coils or steel bars.

Easy to be used, ITA 41 is equipped with its three-position suspension hook to ensure a lighter and more comfortable strapping operation.

Powerful, fast and robust, the ITA 41 is manufactured to be durable and with low maintenance required.



FEATURES

Double Notch Seal Joint
Manual Tensioning operation
3 Operating Buttons
Strong and Reliable
Easy to be used

BENEFITS

Robust and durable
For a wide range of steel Straps
Low Maintenance Required
Powerful and Fast
Suspension hook already equipped

TECHNICAL SPECIFICATION

Dimensions	430 x 260 x 310 mm
Weight	10,3 Kg

STRAP

Type	Steel Strap - regular & high tensile
Width	19mm / 25mm / 32mm
Thickness	0,6mm ÷ 1,0mm (Regular duty) 0,63mm ÷ 0,8mm (High Tensile)

POWER SUPPLY

Pressure Range	5.5 - 7 bar (78 - 99 psi)
Air Consumption	12 L/s - 25 cuft/min

PERFORMANCE

Max. tension force	9000N (19mm version) 15000N (25mm / 32mm versions)
Tensioning Speed	3,8 mt/min - 9000N 5,2 mt/min - 15000N
Sealing	Seal Double Notch
Joint Strength	75% of breaking strength

* variable according to strap type

MODEL

CODE	DESCRIPTION
T411943	ITA 41 - 19mm Steel - 9000N
T412543	ITA 41 - 25mm Steel - 15000N
T413243	ITA 41 - 32mm Steel - 15000N