Semi-Automatic Stretch Wrapper

ROTOPLAT 508 DW - DW/C

SEMI AUTOMATIC STRETCH WRAPPER

5 YEAR WARRANTY

Made to properly contain doors,windows, and other finished and semi-finished products in this industry.

- AVAILABLE WITH MANUAL PRODUCT LOCK SYSTEM (DW) OR IDLE ROLLERS CONVEYOR (DW/C).

  71" DIAMETER TURNTABLE.
- WRAPS ITEMS WITH A THICKNESS OF 1.5" TO 14" THICK; 30" TO 70" WIDE; AND 42" TO 110" HIGH.
- ADJUSTABLE BRACKETS ALLOW YOU TO WRAP DIFFERENT SIZES.
- PDS FILM CARRIAGE DELIVERS 250% PRE-STRETCH USING FIXED GEARS. BY ACTIVATING THE “DOUBLE STRETCH” CONTROL, THE CARRIAGE CAN SWITCH TOVARIABLE PRE-STRETCH VIA A CLUTCHPOSITIONED ON THE FIRST ROLLER.
- CONTAINMENT FORCE ADJUSTABLE FROM COLOR TOUCHSCREEN CONTROL PANEL. PATENTED HIGH-PERFORMANCE S-WRAP PATTERN (WITH QUICK LOAD SYSTEM) AND LOAD CELL COMPENSATION AND CONTAINMENT FORCE GIVE YOU TOTAL FILM CONTROL.
- FOOT PEDAL CONTROLS TOP PLATEN, ALLOWING OPERATOR TO HOLD DOOR IN PLACE, WHILE LOWERING CLAMP TO SECURE PRODUCT.

ROBOPAC USA

PERFORMANCE FEATURES:

COLOR TOUCH SCREEN

The high performance 7-inch color touch screen with icons specifically designed and created by Robopac has led to the implementation of the MULTILEVEL CONTROL function.

PDS CARRIAGE

PDS Carriage with dual pre-stretch rollers controlled via the control panel. Pre-stretch system stretch ratio adjustable from panel board up to 250%.

TURNTABLE DW

Manual product lock system.



TURNTABLE DW/C

Idle rollers conveyor and manual product lock system.

ROTOPLAT 508 DW - DW/C SPEC SHEET

ROBOPAC USA

Load Capacity:

-Turntable Size: 71” Diameter

-Maximum Load Height: 65” (L) x 8” (W) x 98" (H)

-Maximum Load Weight: 220 lbs. (DW), 330 lbs. (DW/C)

Film Delivery System

-Standard Pre-stretch: Variable 0 – 250%

-Containment Force: Multi-Level Variable

-Film Carriage Motor: ½ HP VAC

-Height Sensing: Automatic via photocell

-Film Threading: Patented S-Pattern

-Corner Compensation: Load Cell

Performance Criteria

-Turntable Speed: 5 – 12 RPM

-Turntable Drive: 1 HP VAC

Utility Requirements

-Voltage: 120V, 14 A, 60 Hz, 1 PH

Safety Features

-Anti-fall device on carriage

-Pressure activated safety stop on carriage

-CE Compliant, UL, CUL

ROBOPACUSA.COM

INFO.US@ROBOPAC.COM